



- Ethernet-Switch • Digital input for encoder (optional) • Line IN/OUT (optional)
- Potential separation between the interfaces themselves

Specification	
Graphic display	Q - 5,7" TFT LCD, 320 x 240 pixel, 262 k colours or V - 5,7" TFT LCD, 640 x 480 pixel, 262 k colours
Input	Touchscreen resistiv
Audio	Beeper, optional: audio IN, audio OUT
Processor	32 Bit Cortex-A8 RISC CPU 600 MHz
Memory	256 MB RAM, 512 MB Flash, 1 MB NVRAM
Memory expansion	SD Card, SDHC Card up to 32 GB*
Data buffering	Persistent data in flash, real-time clock and retain data battery- buffered
Software	
Operating system	Microsoft Windows Embedded Compact 7
PLC programming	IEC 61131-3, CODESYS V2.3 or CODESYS V3.x
HMI programming	elaDesign (optional TargetVisu)
C, C++ and C# programming	Microsoft Visual Studio 2005/2008 (Visual C++) with SDK
Interface	
Ethernet	2 x 10/100 BASE-T, RJ45, switch-mode
Field bus interface	1 x CAN acc. ISO 11898 with galvanic isolation, RJ45 1 x CAN acc. ISO 11898 with galvanic isolation, D-Sub-9 plug
Serial interface	1 x RS-232 with galvanic isolation, D-Sub-9 plug 1 x RS-232 and RS-422/RS-485 with galvanic isolation, D-Sub-9 plug
USB	2 x 2.0 Host, type A
Encoder inputs	optional: incremental encoder
Audio	Beeper, optional: Line IN, Line OUT
Order-No.:	
24792.0000	PMC405Q/ED/CS2/elrest
24782.0000	PMC405V/ED/CS2/elrest

Environment/mechanical values	
Supply voltage	24 V DC (18 V...30 V), 8 W...12 W
Housing	Plastic
EMC examinations	EN 61000-6-2, EN 61000-6-4
Environment audit	EN 60068-2-6, EN 60068-2-27
IP Rating	Front IP54, Back IP20 acc. EN 60529
Mounting	With terminal blocks
Outside dimension in mm (W x H x D)	208 x 150 x 53
Cut-out dimension in mm (W x H)	198 x 138
Weight approx.	800 g
Operating temperature	0 °C...50 °C
Storage temperature	-20 °C...70 °C
Relative humidity for operation	10%...85% no condensing
Air pressure (storage)	min. 660 hPa, corresponding to a height of max. 3500m
Air pressure (operation)	min. 795 hPa, corresponding to a height of max. 2000m
Concentration of pollutants (operation/storage)	SO ₂ : < 0,5 ppm; relative humidity < 60 %, no condensation H ₂ S: < 0,1 ppm; relative humidity < 60 %, no condensation
Applications	
	in many industries such as plastics, medical- and automation technology

Illustrations, descriptions, dimensions and specifications correspond to the circumstances or intentions at the time of printing this brochure. Changes of any kind, especially those resulting from technological progress, economic performance or a similar will be without notice. The external interconnection of equipment will be on your own responsibility

***Remark:** The use of standard memory card (e.g. CF-cards) is generally possible. Anyhow elrest GmbH does not take any responsibility thereby.

****Remark:** Plastic housing are subject to minor production tolerances. The specified cabinet dimensions are oriented on the upper tolerance limit to avoid problems by the installation. The other dimensions, including the front panel dimensions, are nominal dimensions

E601106-1.5

elrest Automationssysteme GmbH • Leibnizstraße 10 • 73230 Kirchheim unter Teck • Tel.: +49 (0) 7021 92025-0

© 2015 • www.elrest.de • Alle Rechte vorbehalten

